



**ULTATRON
FRANCE**

**5 YEARS
WARRANTY**

Technical sheet

ULTATRON LiFePO4 Smart BMS Lithium Battery UBL-36-100

Compared with traditional batteries, our lithium iron phosphate batteries (LiFePO4) have many advantages:

- 5 years manufacturer's warranty
- The safest technology, without risk of fire or explosion
- Long service life
- Constantly improving storage capacity
- High stability even under extreme loads
- No memory effect, no need for full charge and discharge cycles
- High performance even under extreme conditions
- Deep and regular discharge and charging efficiency
- Small size and light weight

Integrated Battery Management System (BMS)

To allow the control and the charge of the different elements of an accumulator battery and to protect it against overcharging, overvoltages and overheating.




Note: It can be connected in parallel within 4 pcs. Series connection is not allowed.

Integrated Bluetooth 4.0 monitoring



You have all important battery data always on your smartphone or tablet. The application displays the data in real time.



MARQUE FRANÇAISE





**ULTIMATRON
FRANCE**

TECHNICAL SHEET

UBL SMART BMS SERIE

ULTIMATRON LiFePO4 Smart BMS Lithium Battery UBL-36-100

ELECTRICAL PERFORMANCE

Nominal Voltage	38.4V
Nominal Capacity	100Ah
Capacity @ 20A	300min
Energy	3840Wh
Resistance	$\leq 10 \text{ m}\Omega$ @ 50% SOC
Self Discharge	<3% / Month
Number of Cycles	>6000 @ 80% DoD

CHARGE PERFORMANCE

Recommended Charge Current	20A
Maximum Charge Current	50A
Recommended Charge Voltage	43.8V
Charge Cut-Off Voltage	43.8V(2000ms)
Reconnect Voltage	>41.4V
Balancing Voltage	>38.4V


DISCHARGE PERFORMANCE

Maximum continuous Discharge Current	150A
Peak Discharge Cut-Off Current	500A $\pm$ 60A(250-1000mS)
Discharge Cut-Off Voltage	30V (2000 ms)
Reconnect Voltage	>33.6V
Short Circuit Protection	1400A $\pm$ 160A

TEMPERATURE PERFORMANCE

Discharge Temperature	-20 ~ 55 °C
Charge Temperature	0 ~ 55 °C
Storage Temperature	-20 ~ 35 °C

DIMENSION



Dimension with terminals L522 * W240 * H221mm

MECHANICAL PERFORMANCE

Weight	31.25kg
Terminal Type	M8
Terminal Torque	80 ~ 100 in-lbs (9 ~ 11 N-m)
Case Material	ABS
Ingress Protection Code	IP65
Bluetooth	Bluetooth 4.0 with smartphone App

COMPLIANCE

Certifications	CE UN38.3 UL1642 & IEC62133 ECE R10
Shipping Classification	UN 3480, CLASS 9

ULTIMATRON FRANCE

Add: 286 Rue Charles Gide, 34670 Baillargues, France

info@ultimatron-france.fr

Tel: +33(0)9 50 42 76 17

V1 12.08.25

