




WISHBONE AND MULTILINK SYSTEM COIL SPRING COMPRESSOR

MAX. LOAD
1500 KG



UNIVERSAL

Spring application



- Designed for professional and safe compression of coil springs for wishbone (wishbone) and multi-link (multi-link) suspension. Not suitable for conical and cylindrical helical springs.
- The inclination of the jaws adapts perfectly to the compression of the spring and guarantees a secure grip.
- The ultra compact design makes it possible to use the tool for cars with a small hole in the rear spring control arm down to Ø30 mm. Comes with a unique safety key torque, which makes it easier, safer the operation
- The safety dynamometric extension simplifies the positioning of the tool on the spring and prevents its overload (Max torque 100 Nm).

Brand application

BMW - Citroën - Chevrolet - Chrysler - Ford - Honda - Hyundai - Kia - Mazda - Mitsubishi - Mercedes - Peugeot - Renault - Suzuki - Toyota - VAG (Skoda, Seat) - Volvo etc.

Technical data



Maximum load	1500 Kg / 15000 N
Minimum distance between jaws:	min. 96mm - max 220mm
Maximum travel:	124 mm
Dim. body	Ø29 - L = 225-280mm
Max torque:	100 Nm

The only set on the market capable of handling among others the following coil spring:

BRAND/MODEL	YEAR	FRONT/REAR
Citroen C1	2006-	Rear
Citroen C3	2003-	Rear
Kia picanto	2007-	Rear
Mitsubishi Colt	2007-	Rear
Peugeot 107, 207, 1007	2007-	Rear
Skoda Octavia	2001-	Rear
Skoda Roomster Scout	2008-	Rear
Suzuki Swift, SX4	2007-	Rear
Toyota Aygo	2007-	Rear
VW Touran	2003-	Rear

Others typical application:

BRAND/MODEL	YEAR	FRONT/REAR
BMW Serie 3 (E91)	2007-	Rear
Citroen C4	2006-	Rear
Mercedes Benz Classe C (W202)	1993-2000	Front
Honda Civic, Stream	2007-	Rear
Kia Ceed	2007-	Rear
Mazda 3	2003-	Rear
Mitsubishi Shogun, Pajero	2007-	Rear
Renault Traffic	2007-	Rear
Skoda Fabia	2007-	Rear
Toyota Yaris	2007-	Rear
Volvo V70	2007-	Rear
VW Polo	2007-	Rear





Components

2 x jaws type 1, Ø90-120 mm

2 x jaws type 2, Ø120-140 mm

1 x spring compressor

1 x 6x120 mm screw

2 x locking pin with magnet

4 x safety pin

