


Daugiagyslis varinis maitinimo kabelis su ypač lanksčiu išoriniu PVC apvalkalu.

Gali būti naudojamas patalpose ir lauke, sausoje ir drėgnoje aplinkoje.



Nuoroda		056107	056091	056121	056114	056145	056138	056169	056152	056183	056176
Spalva		●	●	●	●	●	●	●	●	●	●
Skerspjūvis (mm ²)		10	16	25	35	50					
Izoliacijos storis		1,4	1,4	1,5	1,7	1,7					
Kabelio Ø (mm)		7,3	8,7	10,5	12,0	13,8					
Gijos	Skaičius	288	204	324	444	636					
	Ø (mm)	0.2	0,3	0,3	0,3 0,3	0,3					
Srovės pralaidumas esant 20 °C	Apvalkalas	50	65	85	106	129					
	Laisvasis klojimas	57	73	97	121	145					
Varža esant 20 °C (Ω/km)		1,91	1,31	0,85	0,595	0.419					
Bendras svoris (kg/km)		130	200	300	410	565					
Ženklinimas		HI-FLEX "dydis" MM ² CE MADE IN EC									
Medžiaga izoliacija		PVC									
Darbinė temperatūra	mobilus	+5°C / +70°C									
	stacionarus	-30°C / +70°C									
Vardinė įtampa U ₀ / U		450 / 750V									
Lenkimo spindulys	mobilusis	4 x kabelio Ø									
	stacionarusis	3 x kabelio Ø									
		20m									
Standartas		IEC60332-1 / CEI EN 50265									

