


Daudzdzīslu vara strāvas kabelis ar īpaši elastīgu PVC ārējo apvalku.

Var izmantot gan telpās, gan ārā, sausā un mitrā vidē.



Ref.		056107	056091	056121	056114	056145	056138	056169	056152	056183	056176
Krāsa		●	●	●	●	●	●	●	●	●	●
Šķērsgriezums (mm ²)		10	16	25	35	50					
Izolācijas biezums		1,4	1,4	1,5	1,7	1,7					
Kabeļa Ø (mm)		7,3	8,7	10,5	12,0	13,8					
Dzīslas	Skaitis	288	204	324	444	636					
	Ø (mm)	0.2	0,3	0,3	0,3 0,3	0,3					
Strāvas caurlaides spēja pie 20°C	Apvalks	50	65	85	106	129					
	Vaļēja ievēlšana	57	73	97	121	145					
Pretestība pie 20°C (Ω/km)		1,91	1,31	0,85	0,595	0.419					
Kopējais svars (kg/km)		130	200	300	410	565					
Markējums		HI-FLEX "izmērs" MM ² CE MADE IN EC									
Materiāls izolācija		PVC									
Darba temperatūra	mobīlā	+5°C / +70°C									
	fiksētā	-30°C / +70°C									
Nominālais spriegums U ₀ / U		450 / 750V									
Lieces rādiuss	mobīlais	4 x kabeļa Ø									
	stacionārais	3 x kabeļa Ø									
		20m									
Standarts		IEC60332-1 / CEI EN 50265									

