


Daudzdzislu vara strāvas kabelis ar īpaši elastīgu PVC ārējo apvalku.

Var izmantot gan telpās, gan ārā, sausā un mitrā vidē.



Ref.		054882	054875	054905	054899	054929	054912	054943	054936	054967	054950	-	056565
Krāsa		●	●	●	●	●	●	●	●	●	●	●	●
Šķērsgriezums (mm ²)		10		16		25		35		50			70
Izolācijas biezums (mm)		1,4		1,4		1,5		1,7		1,7 1,7			1,9
Kabeļa Ø (mm)		7,3		8,7		10,5		12,0		13,8			15,9
Stieples	Skaits	288		204		324		444		636			900
	Ø (mm)	0,2		0,3		0,3 0,3		0,3		0,3			0,3 0,3
Strāvas caurlaides spēja pie 20°C (A)	ar ārējo apvalku	50		65		85		106		129			164
	bez ārējā apvalka	57		73		97		121		145			184
Pretestība pie 20 °C (Ω/km)		1,91		1,31		0,85		0,595		0,419			0,297
Svars (kg uz 100 m)		13		20		30		41		56,5			78
Marķējums		HI-FLEX "izmērs" MM ² CE											
Izolācijas materiāls		PVC											
Darba temperatūra	pārvietojams	+5°C / +70°C -30°C / +70°C											
	fiksētā												
Nominālais spriegums U ₀ / U		450 / 750V											
Liekuma rādiuss	mobīlā	4 x kabeļa Ø 3 x kabeļa Ø											
	fiksētā												
		100 m										50 m	
Standarta		IEC60332-1 / EN 60332-2-1:2004											