



REAR DRIVE MOTOR COOLANT RESERVOIR REMOVAL SOCKET **AUDI**




- Specially designed cup socket used to remove and refit the coolant leakage container (expansion tank) without causing damage to the rear drive motor on the Audi e-tron, at the required service intervals recommended by the vehicle manufacturer.



PLUS

Manufactured from non-conducting nylon composite to help prevent damage to the vehicle component.



Technical data

- Flutes: 12; 60mm diameter.
- Use with 27mm single hex socket.

Application

Equivalent to OEM T40409. Designed to fit leakage container OEM 0EF901257C.





TOOL FOR INSTALLING WATER PUMP STRETCH BELT WITHOUT BELT TIGHTENER **PSA/OPEL**



- Tool for installing water pump stretch belt without belt tightener. For use for PSA and Opel group vehicles engines 1.0 - 1.2.




AIR CONDITION BELT INSTALLATION TOOL FOR **BMW** **N62 / MINI W17**



- For installation of stretch belts (drive belts without tensioner) suitable for stretching belts on BMW N62 (V8) (2004-2006) and MINI W17 (Diesel)

Application

PEUGEOT	108, 208, 301, 308, 408, 2008, 3008, 5008, Partner C1, C2, C3 Picasso, C3 Aircross, C4, C4 Picasso, C4 Cactus, C-Elysee, Berlingo, DS 3, DS 4, DS 4S, DS 5LS	2012	1.0L and 1.2L 3-cylinder engines	EN-521122; 0109-1B; 0109-B
CITROËN				
VAUXHALL/OPEL	Crossland X			



Application

MINI	To be used as OEM2	64 1 040
BMW	To be used as OEM1	

