



16T MECHADRAULIC SCREW ADAPTOR KIT



PLUS

THE SET INCLUDES 5 SPARE SAFETY PINS. THE SAFETY PINS AVOID DAMAGING THE TOOL IN CASE THE MAXIMUM TORQUE HAS BEEN REACHED, PIN WILL BREAK. IN THIS WAY THE TOOL CANNOT BE DAMAGED.



- Due to the mechanical properties, shape and size, the Govoni Mechadraulik- Spindle is optimally suited for use in the automotive sector: removal and installation of wheel hubs, drive shafts, supporting joints, tie rod heads, pitman arms, silent bearings etc.
- The 1-1/2 inch x 16 tpi receiving thread is one of the most commonly used special tool threads.

Technical data

Force:	16ton
Dimensions	Ø38x225x345
Driving torque	38 Nm
Receiving thread	1-1/2"-16G
Stroke	20 mm

Compatible with the following systems

- Würth
- Nexus
- Müller
- Pichler
- Sykes Pickavant
- Sauer
- KS Tools
- Facom, ecc...



COMPLETA CON SET DI INSERTI PER VITE MECADRAULICA

Application

VAG: e.g. drive shaft made of steel and aluminium, Golf 5 and Golf 6.
Wheel hubs with small internally splined profile from 21 mm



- Used in conjunction with the 16 ton mechadraulic screw **GO1016** to extract drive shafts, cv joints and bearings; can be used to prolong the thrust action.




CODE **1014**

1 with 2 pcs.

kg 0,4 Kg

Components

- 1 x Ø20 pulling adaptor
- 1 x Ø24 pulling adaptor



CODE **1016**

1 with 12 pcs.

kg 2,2 kg

