

G 20T HYDRAULIC CYLINDER 8 MM, STEEL



Technical data

- Dimensions: Ø100x60 mm
- Pressure: max. 700 bar
- Hole: Ø33 mm
- Connection: 3/8" -18 NPT
- Adapter: Ø20 mm

G 32T HYDRAULIC CYLINDER 50 MM, STEEL



Technical data

- Dimensions: Ø104x261 mm
- Pressure: max. 700 bar
- Hole: Ø21.5 mm
- Connection: 3/8" -18 NPT
- Inner thread: M24x2
- Outside connection thread: 2" 3/4-16 UN

GLOCK
HYDRAULIC

GO CODE **1020**

1 with 2 pcs. 3 kg

QUICK
HYDRAULIC

GO CODE **1020Q**

1 with 2 pcs. 3 kg

GLOCK
HYDRAULIC

GO CODE **1032**

1 with 1 pcs. 11,8 kg

QUICK
HYDRAULIC

GO CODE **1032Q**

1 with 1 pcs. 11,8 kg

G 32T HYDRAULIC CYLINDER 50 MM, ALUMINIUM



Technical data

- Dimensions: Ø104x261 mm
- Pressure: max. 700 bar
- Hole: Ø21.5 mm
- Connection: 3/8" -18 NPT
- Inner thread: M24x2
- Outside connection thread: 2" 3/4-16 UN

GLOCK
HYDRAULIC

GO CODE **1070**

1 with 1 pcs. 8,6 kg

QUICK
HYDRAULIC

GO CODE **1070Q**

1 with 1 pcs. 8,6 kg

G SPINDLE M20



Application

To be used with
GO015, GO017

- To be use with the hydraulic cylinders.

GO CODE **016**

1 with 5 pcs. 1,6 kg

G SPINDLE M24



Application

To be used with GO040

- To be use with the hydraulic cylinders.

GO CODE **041**

1 with 3 pcs. 1,6 kg