



UNIVERSAL KIT BUSH AND BEARING REMOVAL PRESS AND PULL SLEEVE Ø INT. 24/14 mm - ØEST. 42/32mm



- This range is used for removing and fitting bearings, bushes, sleeves, sealing rings etc.
- Can be used mechanically or with optional hydraulics.
- Sleeves can be machined mechanically and optimally adapted to the work task.
- Use on vehicle, workshop press, C-frame, vice etc.
- Minimal friction due to integrated thrust bearing.

GO CODE **143**
T with 24 pcs. kg 19 Kg

+ 12T MECHADRAULIC CYLINDER-SET ALUMINIUM



Technical data

- Force: 12 ton
- Stroke: 8 mm
- Dimensions: Ø80x260x45 mm
- Pressure: max. 700 Bar
- Hole: Ø21.5 mm
- Driving torque: 56 Nm
- Weight: 1,65 kg
- Grease temperature range of

use: from -25°C to 80°C

- Material: aluminium
- Adaptors: M10/M12/M14/
M16/M18

GO CODE **1015**
T with 7 pcs. kg 1,8 kg
§ **PATENTED**

+ 17T HYDRAULIC CYLINDER, 43 MM, ALUMINIUM



Technical data

- Dimensions: Ø90x155 mm
- Pressure: max. 700 Bar
- Connection: 3/8" -18 NPT
- Outside connection thread:
2" 3/4-16 UN

- Adaptors: M10/M12/M14/M16/
M18

GOLOCK
HYDRAULIC
GO CODE **1061**
T with 7 pcs. kg 2,2 kg
§ **PATENTED**

GOQUICK
HYDRAULIC
GO CODE **1061Q**
T with 7 pcs. kg 2,2 kg
§ **PATENTED**