



MACPHERSON STRUT SUPPORT FOR JACK CAPACITY 120 KG



- Can be used to support the shock absorber when the suspension arm is removed. The shock absorber support is used together with a standard transmission jack. Used to prevent the shock absorber from sinking when removed from the handlebar arm.
- What is new is the adapter plate for the fork attachment Ø60mm, which extends the field of application.
- The supply includes two mounting sleeves for Ø25 and 30 mm piston rods.



Components

1 x Macpherson strut support
1 x safety bracket 80 mm
1 x reduction for strut support to 60 mm
1 x Ø 25 mm adapter
1 x Ø 30 mm adapter



CODE **316**

T with 3 pcs.

Kg 3 Kg



PLUS:
the new adapter plate
extends the field of
application!




STUB AXLE PROP UNIVERSAL



- The universal wheel hub holder is V-shaped and therefore can be fixed on the bolts of all hubs, designed to be coupled with the bolts that secure the wheels.
- The kit include the adapters for hydraulic pit jacks piston rod Ø 25 and 30mm.
- Compatible with approximately 95% of hydraulic pit jacks, thanks to the adapters for various piston rod diameters supplied with the kit.

Application

1. Disassembly and assembly of the upright and the support joint or trapezoid of the suspension cross arm.
2. Load bearing test according to manufacturer specifications to highlight noise.



Technical data

- Max. load: 330 kg
- Total length: 225 mm
- Assembly: Ø40mm
- Tilt angle: $\pm 46^\circ$ (forwards + backwards)
- For wheel bolts: max. M16



CODE **366**

T with 3 pcs.

Kg 1,5 Kg



MAX LOAD
330 Kg

FOR WHEEL BOLTS
MAX: **M16**

Application

- With cone or spherical collar attachment
- The V-shaped prop rotates by 46° and can be locked in a central position

On request:
**GO1450, GO1451,
GO1452, GO1453**