

+ INJECTOR ADAPTOR SET DELPHI, DENSO, BOSCH, SIEMENS

- The disassembling screw adapter helps to create a stressed, forcecoupled connection between the injector and the sliding rod or the glow plug. In this way the extractors can be extracted with high impact and hydraulic forces.
- The double adapters are simultaneously adjusted internally on the screwing ring thread and externally on the screwing of the nozzle head. The accessory allows connection with the traction systems available.



CODE	THREAD	DESCRIPTION	QUANTITY
311 146 011	M18x1.5	Screw L=220 mm	1 pcs.
311 070 006	M18x1.5	Nut CH30	1 pcs.
311 083 004		Washer with bearing	1 pcs.
311 166 008	M-F M18x1.5	Extension	1 pcs.
311 166 007	F-F M18x1.5	Extension	1 pcs.
311 146 017	M27x1	Adapter (SIEMENS)	1 pcs.
311 146 016	M25x1	Adapter (SIEMENS)	1 pcs.
311 146 013	M14x1.5	Adapter (DELPHI)	1 pcs.
311 146 014	M16x1	Adapter (DENSO)	1 pcs.
311 146 015	M20x1	Adapter (DENSO)	1 pcs.
311 166 005	Int. M17x1 - Ext. M27x1	Adapter (BOSCH)	1 pcs.
311 198 000	Int. M14x1 - Ext. M25x1	Adapter (SIEMENS)	1 pcs.
311 199 000	Int. M14x1 - Ext. M25x0,75	Adapter (DENSO)	1 pcs.
311 210 000	Int. M20x1 - Ext. M25x0,5	Adapter (DENSO)	1 pcs.



Application

The set allows you to adapt about 90% of all injectors.

GO CODE **427**
1 with 14 pcs. 3,2 kg

G INJECTOR REMOVAL SOCKET 2.0 ECOBBLUE TDCI, FORD



Application

Ford 2.0 ecoblue TDCI from 2016 (Ford Galaxy, S-max, Mondeo, Focus C-Max, Transit and Custom (from 2018) etc

GO CODE **519**
1 with 1 pcs. 0,6 kg

Engine code

YLF6, YLF6, YMFS, YMF6, YNFS, YNF6, YLR6, YMR6, YNR6

G INJECTOR EXTENSION ADAPTER 2.0L DW10FC+DW10FU



- Tool for the mechanical removal of injectors using a slide hammer or a standard pneumatic impact puller.
- No partial disassembly required. The injector can be reused afterwards.



GO CODE **566**
1 with 1 pcs. 0,6 kg