



TOOL FOR ABSORBED PUMP RING NUT FCA



- Tool for disassembling / tightening the absorbed pump fixing ring nut.

GO CODE **619**
1 with 1 pcs. 0,3 kg

Application

Brand	Model	Engine
FIAT	500L - 500X - Panda (dal 2012) - Freemont - Tipo (from 2015)	0.9 TwinAir, 1.3 MJ, 1.4 Fire/T-Jet, 1.4 MultiAir/TurboJet, 1.6 MJ, 1.6 E-torq, 2.0 MJ, 2.4, 3.6 V6
	JEEP Renegade	1.6 E-torq, 1.6 MJ, 2.0 MJ
LANCIA	Ypsilon	0.9 TwinAir, 1.3 MJ
ALFA ROMEO	Mito - Brera - Giulietta - 159 - Giulia - Stelvio - Spider	0.9 TwinAir Turbo, 1.3 JTDM, 1.4 Turbo MultiAir/TJet, 1.6 JTDM, 2.0 JTDM, 2.0, 2.2 D, 2.4 JTDM

OEM

2.000.002.100



OIL FILTER REMOVER SET FOR FCA GROUP, OPEL, SUZUKI, 1.3 MJ



- This 3-legs special tool and the support allow to assemble and disassemble the plastic lock nut of the new filters on Fiat Multijet.

GO CODE **641**
1 with 1 pcs. 1 kg

Application

FIAT	Punto Panda Idea Stylo Doblo	1.3 Multijet 16v
	Ducato	2.0 8V JTD; 2.2 16V JTD; 2.3 16V JTD; 2.3 16V JTD; 2.8 JTD; 3.0 16V
LANCIA	Ypsilon Musa	1.3 Multijet 16v
OPEL	Corsa Agila	1.3 CDTI
SUZUKI	Ignis Vagon R+	1.3 DDiS 16v

